## **SAT Report**

PMN Number: L-13-0170 SAT Date: 2/26/2013 Print Date: 11/26/2014



### **Concern levels:**

Type of Concern: <u>Health</u> <u>Eco</u> <u>Comments</u>

Level of Concern: 1-2

| <b>Persistence</b> | <b>Bioaccum</b> | <b>Toxicity</b> | <b>Comments</b> |
|--------------------|-----------------|-----------------|-----------------|
| 3                  | 2               | 1               |                 |
|                    |                 | Awaiting        |                 |
|                    |                 | Human Health    | ı               |
|                    |                 | Entry           |                 |
|                    |                 | Awaiting        |                 |
|                    |                 | Human Health    | ı               |
|                    |                 | Entry           |                 |
|                    |                 | Awaiting        |                 |
|                    |                 | Human Health    | ı               |
|                    |                 | Entry           |                 |

## **Exposure Based Review:**

Health: No Ecotox: No

Routes of exposure: Health: Dermal Inhalation

**Ecotox:** No releases to water

Fate: ;

**Keywords:** 

**Keywords:** 

# **Summary of Assessment:**

Fate:

Fate Summary: L-13-0170

FATE:

Liquid with MP < -80 C (M)

 $\log Kow = 6.28 (E)$ 

S = 0.012 mg/L at 25 C (E)

VP = 69 torr at 25 C (M)

BP = 84 C (M)

H = 9.67E + 4 (E)

 $\log Koc = 5.55 (E)$ 

log Fish BCF = 3.81 (E)

log Fish BAF = 6.17 (E)

POTW removal (%) = 90-99 via sorption and stripping

Time for complete ultimate aerobic biodeg > mo

Sorption to soils/sediments = v.strong

Volatilization half-life from a standard river = 2 hrs

Volatilization half-life from a standard lake = 8 da

PBT Potential: P3B2

\*CEB FATE: Migration to ground water = negl

### **Health:**

| <b>Health Summary:</b> Absorption is poor all routes based on physical/chemical                    |
|--|
| properties. The Standard Review for properties (perfluorodimethylcyclohexane                       |
| derivatives) supported a concern for neurotoxicity at high exposure levels. The Standard Review    |
| did not support concern for liver effects based on the lack of liver toxicity in the acute study   |
| submitted for ; cardiac sensitization based on evidence in the literature that                     |
| increasing the degree of fluorination of a chemical decreases the cardiac sensitization potential; |
| developmental/reproductive toxicity because there were no close analogs that have been shown       |
| to cause developmental or reproductive toxicity. New information since the Standard Review         |
| for shows that octafluoropropane is positive for cardiac sensitization in 1 of 6                   |
| dogs at 40% concentration in the air with no response at 30% concentration or less.                |
| This is not considered to be a close analog because it is much smaller than the LVE compound.      |
| The nonreactivity and chemical stability of perfluorocarbons lead to a concern about high global   |
| warming potential and long atmospheric lifetimes. Low moderate concern.                            |

## **Ecotox:**

| Test Organism | Test | Test End      | Predicted | Measured | Comments |
|---------------|------|---------------|-----------|----------|----------|
|               | Type | Point         |           |          |          |
| fish          | 96-h | LC50          | *         |          |          |
| daphnid       | 48-h | LC50          | *         |          |          |
| green algal   | 96-h | EC50          | *         |          |          |
| fish          | _    | chronic value | *         |          |          |
| daphnid       | _    | chronic       | *         |          |          |
|               |      | value         |           |          |          |
| algal         | _    | chronic       | *         |          |          |
|               |      | value         |           |          |          |
| Sewage Sludge | 3-h  | EC50          | _         |          |          |
| Sewage Sludge | _    | Chronic       |           |          |          |
|               |      | Value         |           |          |          |

# **Ecotox Values Comments:**

| Factors                  | Values                    | Comments |
|--------------------------|---------------------------|----------|
| Assessment Factor        | 10                        |          |
| Concentration of Concern |                           | *        |
| (ppb)                    |                           |          |
| SARs                     | neutral organic chemicals |          |
| SAR Class                | fluorocarbon              |          |
| Ecotox Category          |                           |          |

## **Ecotox Factors Comments:**

**SAT Chair:** Becky Jones

1

## **Focus Report**

New Chemicals Program PMN Number: L-13-0170

Focus Date: 03/11/2013 12:00:00 AM Report Status: Completed Consolidated Set: Focus Chair: Kristan Markey Contractor: Bryan Amagai I. Notice Information Submitter: 2690-05-3 Johnson Matthey Inc. CAS Number: Chemical Name: Pentane, 1,1,1,2,2,3,4,4,5,5,5-undecafluoro-3-(1,1,2,2,2-pentafluoroethyl)-Use: Tracer chemical used to measure flow in deep oil and gas bearing strata or hydrocarbon leak measurements. P2 Claim: This chemical is intended to replace radionuclide tracers. . No references were found for this use. However, analogs all have this use. Other Uses: 1,000 Kg/yr PV-Max: **Binding Option:** Yes Import: Manufacture: X SAT Results (1) Health Rating: **Eco Rating:** Comments: Non-Occupational: Environmental: 2 Occupational: 2-3A (1) **PBT:** 3 1 Comments: III. OTHER FACTORS Categories: Health Chemical Category: Ecotox Category: neutral organic chemicals Related Cases/Regulatory History: Health related Cases: Ecotox Related Cases: Same as . Analogs: Regulatory History: 3) - GRANTED WITH CONDITION (Same As ) - GRANTED WITH CONDITION (Same As - GRANTED WITH CONDITION (Same As GRANTED WITH CONDITION - GRANTED WITH LETTER GRANTED GRANTED WITH CONDITION - WITHDRAWN - OTHER - WITHDRAWN/FACE 5E ) - GRANTED WITH CONDITION (Same as - GRANTED - GRANTED WITH CONDITION MSDS/Label Information: MSDS: Label: No None listed. General Equipment:

Respirator: None listed.
Health Effects: Not classified.
TLV/PEL (PMN or raw - None established.

material):

LVEPPE: Goggles, Fume hood with adequate air face velocity of 100 feet per minute, Impervious gloves,

Tyvek Suit

## Exposure Based Information:

Exposure Based Review: N Exposure Based Review (Health): N

Exposure Based Review (Eco): N Exposure Based Review (Non Occupatuional):

Exposure Based (Occupational): No Exposure Based (Environmental):

#### IV. Summary of SAT Assessment

#### Fate:

**Fate Summary:** L-13-0170

FATE:

Liquid with MP < -80 C (M)

 $\log Kow = 6.28 (E)$ S = 0.012 mg/L at 25 C (E)VP = 69 torr at 25 C (M)

BP = 84 C (M)H = 9.67E + 4 (E) $\log Koc = 5.55 (E)$  $\log$  Fish BCF = 3.81 (E)  $\log \text{ Fish BAF} = 6.17 (E)$ 

POTW removal (%) = 90-99 via sorption and stripping

Time for complete ultimate aerobic biodeg > mo

Sorption to soils/sediments = v.strong

Volatilization half-life from a standard river = 2 hrs Volatilization half-life from a standard lake = 8 da

PBT Potential: P3B2

\*CEB FATE: Migration to ground water = negl

#### Health:

**Health Summary:** 

Absorption is poor all routes based on physical/chemical properties. The Standard Review for supported a concern for neurotoxicity at high exposure levels. The Standard Review did not support concern for liver effects based on the lack of liver toxicity in the acute study submitted for ; cardiac sensitization based on evidence in the literature that increasing the degree of fluorination of a chemical decreases the cardiac sensitization potential; developmental/reproductive toxicity because there were no close analogs that have been shown to cause developmental or reproductive toxicity. New shows that information since the Standard Review for positive for cardiac sensitization in 1 of 6 dogs at 40% concentration in the air with no response at . This is not considered to be a close analog because it is 30% concentration or less much smaller than the LVE compound. The nonreactivity and chemical stability of perfluorocarbons lead to a concern about high global warming potential and long atmospheric lifetimes. Low moderate concern.

#### **Ecotox:**

**Ecotox Values:** 

Fish 96-h LC50: \*(P) Daphnid 48-h LC50: \*(P) Green algal 96-h EC50: \*(P) Fish Chronic Value: \*(P) Daphnid ChV: \*(P) Algal ChV: \*(P)

**Ecotox values comments:** Predictions are based on SARs for neutral organic chemicals; SAR chemical class = fluorocarbon; MW 388; log Kow ~ 6 (ACD); liquid with mp unknown (P); S < 0.001 mg/L at 25 C (P); pH7; effective concentrations based on 100% active ingredients and mean measured concentrations; hardness <180.0 mg/L as CaCO3; and TOC <2.0 mg/L;

**Ecotox Factors:** 

Assessment Factor: 10 Concern Concentration:

# V. Summary of Exposures/Releases Engineering Summary: L-13-0170

| Exposures/Releases       | Release  | Release  | Release  |
|--------------------------|--|--|--|
| Scenario                 | Processing:                                      | Processing:  | Processing:  |
|                          | Repackaging/Formulation                          | Repackaging/Formulation  | Repackaging/Formulation  |
| Sites                    | 1  | 1  | 1  |
| Media                    | Air  | Water or Incineration or<br>Landfill   | Air  |
| Descriptor A             | Typical  | High End   | Output 2   |
| Quantity A (kg/site/day) | 7.4E-2   | 3.0E-1   | 7.1E-1   |
| Frequency A (day/year)   | 20   | 20   | 20   |
| Descriptor B             | Worst Case                                       |  |  |
| Quantity B (kg/site/day) | 7.4E-2   |  |  |
| Frequency B (day/year)   | 20   |  |  |
| From                     | Unloading Liquid Raw<br>Material from Containers | Cleaning Liquid Residuals<br>from Containers Used to<br>Transport the Raw Material | Cleaning Liquid Residuals<br>from Containers Used to<br>Transport the Raw Material |
| Workers                  |  |  |  |
| Exposure Type            |  |  |  |

| Engineering Summary:<br>Exposures/Releases | Release  | Release                                    | Release  |
|--|--|--|--|
| Scenario                                   | Processing:<br>Repackaging/Formulation                           | Processing:<br>Repackaging/Formulation     | Use: Injection of Tracer<br>Chemical into Oil-Bearing<br>Strata                    |
| Sites                                      | 1  | 1  | 1  |
| Media                                      | Water or Incineration or<br>Landfill                             | Air  | Water or Incineration or Landfill  |
| Descriptor A                               | Conservative   | Typical                                    | High End   |
| Quantity A (kg/site/day)                   | 5.0E-1   | 9.1E-2                                     | 1.2E-1   |
| Frequency A (day/year)                     | 20   | 20   | 50   |
| Descriptor B                               |  | Worst Case                                 |  |
| Quantity B (kg/site/day)                   |  | 1.8E-1                                     |  |
| Frequency B (day/year)                     |  | 20   |  |
| From                                       | Equipment Cleaning Losses of Liquids from a Single, Small Vessel | Loading Liquid Product into 5 L Containers | Cleaning Liquid Residuals<br>from Containers Used to<br>Transport the Raw Material |
| Workers                                    |  |  |  |
| Exposure Type                              |  |  |  |

# V. Summary of Exposures/Releases Engineering Summary: L-13-0170

| Exposures/Releases       | Release                   | Release                   | Exposure                 |
|--------------------------|---------------------------|---------------------------|--------------------------|
| Scenario                 | Use: Injection of Tracer  | Use: Injection of Tracer  | Processing:              |
|                          | Chemical into Oil-Bearing | Chemical into Oil-Bearing | Repackaging/Formulation  |
|                          | Strata                    | Strata                    |                          |
| Sites                    | 1                         | 1                         | 1                        |
| Media                    | Air                       | Incineration              | Dermal                   |
| Descriptor A             | Typical                   | Output 2                  | High End                 |
| Quantity A (kg/site/day) | 2.9E-2                    | 2.0E+1                    | 1.7E+3                   |
| Frequency A (day/year)   | 50                        | 50                        | 20                       |
| Descriptor B             | Worst Case                |                           |                          |
| Quantity B (kg/site/day) | 2.9E-2                    |                           |                          |
| Frequency B (day/year)   | 50                        |                           |                          |
| From                     | Unloading Liquid Raw      | Oil Production            | Unloading Liquid Raw     |
|                          | Material from Containers  |                           | Material from Containers |
| Workers                  |                           |                           | 3                        |
| Exposure Type            |                           |                           | Liquid                   |

| Engineering Summary:<br>Exposures/Releases | Exposure   | Exposure                                   | Exposure                                   |
|--|--|--|--|
| Scenario                                   | Processing:<br>Repackaging/Formulation           | Processing:<br>Repackaging/Formulation     | Processing:<br>Repackaging/Formulation     |
| Sites                                      | 1  | 1  | 1  |
| Media                                      | Inhalation                                       | Dermal                                     | Inhalation                                 |
| Descriptor A                               | Worst Case                                       | High End                                   | Worst Case                                 |
| Quantity A (kg/site/day)                   | 1.1E+3   | 7.1E+2                                     | 2.6E+3                                     |
| Frequency A (day/year)                     | 20   | 20   | 20   |
| Descriptor B                               | Typical  |  | Typical                                    |
| Quantity B (kg/site/day)                   | 3.5E+1   |  | 4.4E+1                                     |
| Frequency B (day/year)                     | 20   |  | 20   |
| From                                       | Unloading Liquid Raw<br>Material from Containers | Loading Liquid Product into 5 L Containers | Loading Liquid Product into 5 L Containers |
| Workers                                    | 3  | 3  | 3  |
| Exposure Type                              | Vapor  | Liquid                                     | Vapor                                      |

# V. Summary of Exposures/Releases Engineering Summary: L-13-0170

| Exposures/Releases       | Exposure  | Exposure  |   |
|--------------------------|---|---|---|
| Scenario                 | Use: Injection of Tracer<br>Chemical into Oil-Bearing<br>Strata | Use: Injection of Tracer<br>Chemical into Oil-Bearing<br>Strata |   |
| Sites                    | 1   | 1   |   |
| Media                    | Dermal  | Inhalation  |   |
| Descriptor A             | High End  | Worst Case  |   |
| Quantity A (kg/site/day) | 7.1E+2  | 4.1E+2  |   |
| Frequency A (day/year)   | 50  | 50  |   |
| Descriptor B             |   | Typical   |   |
| Quantity B (kg/site/day) |   | 1.4E+1  |   |
| Frequency B (day/year)   |   | 50  |   |
| From                     | Unloading Liquid Raw<br>Material from Containers                | Unloading Liquid Raw<br>Material from Containers                |   |
| Workers                  |   |   |   |
| Exposure Type            | Liquid  | Vapor   | _ |

#### VI. Focus Decision and Rationale

**Regulatory Actions** 

Regulatory Decision: LVE Final Conditional Grant Decision Date: 03/11/2013

Type of Decision:

Rationale: L-13-0170 was given a final conditional grant based on binding to the

production volume and the uses described in the PMN. Absorption is poor all routes based on physical/chemical properties. Human health hazard concerns were low-moderate based on cardiac sensitization. Workers are expected to be exposed via inhalation and dermal routes. Potential risks to workers were mitigated by appropriate PPE. Ecotoxicity hazard concerns were low based on EcoSAR predictions for neutral organics. Potential risks to the environment were low based on no effects expected at saturation. The submitter bound this

LVE to 1,000 kg/yr, and EPA assessed it at this volume..

COC: No effects at saturation

Summary of Exposures and Releases

Proc

1 site, 20 days/year, 6 workers

Inhalation (Vapor): Typical: 3.5E+1 mg/day, Worst Case: 1.1E+3 mg/day Inhalation (Vapor): Typical: 4.4E+1 mg/day, Worst Case: 2.6E+3 mg/day

Dermal: 1.7E+3 mg/day (98% Liquid) Dermal: 7.1E+2 mg/day (40% Liquid)

Releases to Water: 3.0E-1 kg/site-day over 20 days/yr

Or Incineration or Landfill

Releases to Water: 5.0E-1 kg/site-day over 20 days/yr

Or Incineration or Landfill

Releases to Air: Typical: 7.4E-2 kg/site-day over 20 days/yr, Worst Case:

7.4E-2 kg/site-day over 20 days/yr

Releases to Air: 7.1E-1 kg/site-day over 20 days/yr

Releases to Air: Typical: 9.1E-2 kg/site-day over 20 days/yr, Worst Case:

1.8E-1 kg/site-day over 20 days/yr

Fate Releases to Air:

Stack Air: LADD: 4.34E-06 mg/kg/day ADR: 9.91E-04 mg/kg/day Fugitive Air: LADD: 4.24E-05 mg/kg/day ADR: 2.39E-02 mg/kg/day

Fate Releases to Water (Removal Rate 90%):

SWC: 10.31 ppb

DW: LADD: 8.63E-07 mg/kg/day; ADR: 5.03E-04 mg/kg/day FI: LADD: 2.39E-05 mg/kg/day, ADR: 2.35E-02 mg/kg/day

Use

1 site, 50 days/year, 3 workers

Inhalation (Vapor): Typical: 1.4E+1 mg/day, Worst Case: 4.1E+2 mg/day

Dermal: 7.1E+2 mg/day (40% Liquid)

Releases to Water: 1.2E-1 kg/site-day over 50 days/yr

Or Incineration or Landfill

Releases to Air: Typical: 2.9E-2 kg/site-day over 50 days/yr, Worst Case:

2.9E-2 kg/site-day over 50 days/yr

Releases via Incineration: 2.0E+1 kg/site-day over 50 days/yr

Fate Releases to Air:

Stack Air: LADD: 2.73E-04 mg/kg/day ADR: 2.57E-02 mg/kg/day Fugitive Air: LADD: 3.19E-06 mg/kg/day ADR: 7.28E-04 mg/kg/day

Fate Releases to Water (Removal Rate 90%):

SWC: 11.32 ppb

DW: LADD: 1.15E-06 mg/kg/day; ADR: 5.17E-04 mg/kg/day FI: LADD: 3.20E-05 mg/kg/day, ADR: 1.26E-02 mg/kg/day

P2 Rec Comments:

### **Testing:**

#### **Final Recommended:**

Health:

Eco:

Fate:

Other:

11 21/201 02 19 52 PM